

## DS-2CD2532F-(I)(S)

## 3.0MP Mini Dome Network Camera



### Key features

- Up to 3 megapixel (2048 x 1536) resolution
- Full HD1080p real-time video
- -I: IR LEDs (up to 10m)
- DWDR & 3D DNR & BLC
- Onboard storage (up to 64 GB)
- -S: Audio I/O, Alarm I/O
- IP66 protection
- Vandal-proof housing

### Accessories



DS-1272ZJ-120B  
Wall mount



DS-1270ZJ-120  
Pendant cap for 25x2  
mini dome (thread  
adapters included)

### Specifications

DS-2CD2512F- (I) (S)	
<b>Camera</b>	
Image sensor	1/3" progressive scan CMOS
Min. illumination	0.19lux @ F2.0, AGC on 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	4mm@F2.0, angle of view: 75.8° (2.8mm, 6mm optional)
Lens mount	M12
Day & night	ICR
Digital noise reduction	3D DNR
Wide dynamic range	Digital WDR
Backlight compensation	Yes, zone configurable
<b>Compression standard</b>	
Video compression	H.264 / MJPEG
H.264 compression profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
<b>Image</b>	
Max. image resolution	2048 x 1536
Frame rate	60Hz: 15fps (2048 x 1536), 30fps (1920 x 1080), 30fps (1280 x 720)
Image settings	Saturation, brightness, contrast adjustable through client software or web browser
<b>Network</b>	
Network storage	NAS
Alarm trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception, storage error
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	Flickerless, dual stream, heartbeat, mirror, user authentication, video mask, watermark
<b>Interface</b>	
Communication interface	1 RJ45 10M / 100M ethernet port
On-board storage	Built-in Micro SD card slot, up to 64 GB
<b>General</b>	
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)
Power supply	DC12V ± 10%, PoE (802.3af)
Power consumption	Max. 7W
Impact protection	IEC60068-2-75Eh, 50J; EN50102, up to IK10
Ingress protection level	IP66
IR range	Up to 10m
Dimensions	99.9 x 97.5 x 46.5 mm (3.93" x 3.84" x 1.83")
Weight	250g (0.55 lbs)

### Available models

DS-2CD2532F-I, DS-2CD2532F-IS

\* -S (special order): Audio I/O interface and Alarm I/O interface.

\* -I: IR LEDs, up to 10m.

\* Includes Single Gang Box adapter plate.